FUJITSU

Data Sheet FUJITSU Desktop ESPRIMO Q558

Powerful PC functionality in small package

The FUJITSU ESPRIMO Q558, featuring full desktop PC functionality in a stylish and compact mini PC, is a real eye-catcher on your desk. Up to 9th Gen Intel® Core™ processors provide the performance to meet your daily office needs. The Zero Noise PC function ensures silent operation. With its integrated, energy-efficient power supply and an innovative Low Power Active Mode feature, this mini PC helps reduce your energy bill while ensuring instant communication capabilities in your office. Its compact size and wide range of interfaces make the FUJITSU ESPRIMO Q558 an ideal choice for offices where space saving is critical for the business.

An elegant mini PC for standard office applications

Eye-catching exclusive modern design

■ Fully equipped PC with a volume of ~2.0 liters - based on standard desktop technology

Zero Noise PC

Pleasant working environment due to completely quiet system (solid state disk required)

■ Fan stop in standard operations

Superb usability

Efficient working environment due to a tidy desk with perfect access to front connectors

■ Horizontal or vertical operations and an optional VESA mount, easy upgrade of major components

Always Available Office PC - stay connected and save power

Be ready for instant communication and a significantly reduced energy bill

■ Innovative Low Power Active Mode and energy-efficient, integrated power supply

Manageability and Ease of Use

"'Plug & work" PC that ensures smooth system administration

■ Easy to integrate into existing IT landscapes and reliable DeskView manageability tools











Components

| Operating systems | |
|--------------------------------|---|
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home |
| Operating system notes | Certified for SUSE Enterprise Desktop Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com. |
| Processor | Intel® Core™ i7-8700T processor (6 Cores / 12 Threads, 2.40 GHz, up to 4.0 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-9400T processor (6 Cores / 6 Threads, 1.80 GHz, up to 3.4 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i7-9700T processor (8 Cores / 8 Threads, 2.00 GHz, up to 4.3 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-9500T processor (6 Cores / 6 Threads, 2.20 GHz, up to 3.7 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-9500 processor (6 Cores / 6 Threads, 3.00 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-9400 processor (6 Cores / 6 Threads, 2.80 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) * |
| | Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) |
| | Intel® Pentium® Gold G5420 (2 Cores / 4 Threads, 3.80 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Pentium® Gold G5400 (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610) |
| | *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) |
| Memory modules | 4 GB (1 module(s) 4 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| | 8 GB (1 module(s) 8 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| | 16 GB (1 module(s) 16 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| Hard disk drives (internal) | SSD PCIe, 1024 GB M.2 NVMe module |
| | SSD PCIe, 512 GB M.2 NVMe module |
| | SSD PCIe, 256 GB M.2 NVMe module |
| | SSD PCIe, 1024 GB M.2 NVMe module, SED |
| | SSD PCIe, 512 GB M.2 NVMe module, SED |
| | SSD PCIe, 256 GB M.2 NVMe module, SED |
| | SSD SATA III, 1024 GB, 2.5-inch |
| | SSD SATA III, 512 GB, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| | SSD SATA III, 128 GB, 2.5-inch |
| | SSD SATA III, 64 GB, 2.5-inch |
| | HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch* |
| | HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch |
| Hard disk notes | SSD (Solid State Disk) SED (Self-Encrypting Drive) |
| Graphics | DP to DVI-D (single link) Adapter Cable |
| Drives (optional) | BD Triple Writer SATA ultra slim (tray) |
| | DVD Super Multi ultra slim (tray) |

| Interface add on cards/components (optional) | |
|--|---|
| | M.2 WLAN 802.11ac (2x2) and BT 5, SRD 5.8GHz (dedicated regions only) |
| | Serial Port |

Base unit

| Base unit | ESPRIMO Q558 |
|-------------------------------|--|
| Mainboard | |
| Mainboard type | D3603 |
| Formfactor | proprietary |
| Chipset | Intel® H310 |
| Processor socket | LGA 1151 |
| Processor quantity maximum | 1 |
| Supported capacity RAM (max.) | 32 GB |
| Memory slots | 2 DIMM (DDR4) |
| Memory frequency | 2,666 MT/s |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 MHz depending on processor and memory configuration |
| LAN | 10/100/1,000 MBit/s Realtek RTL8111GN |
| Integrated WLAN | 1 (optional with Bluetooth together) |
| BIOS version | AMI Aptio V UEFI Specification 2.6 |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology |
| Audio type | On board |
| Audio codec | Realtek ALC671 |
| Audio features | Internal speaker supports audio playback (optional), High Definition audio |
| I/O controller on board | |
| Serial ATA total | 2 |
| thereof SATA III | 2 |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI |
| Interfaces | |
| Audio: line-out | 1 |
| Front audio: microphone | 1 |
| Front audio: headphone | 1 |
| USB 2.0 total | 4 |
| USB 3.1 Gen1 (USB 3.0) total | 4 |
| USB front | 2x USB 3.0 |
| USB rear | 4x USB 2.0 and 2x USB 3.0 |
| VGA | optional: via external active adapter cable |
| DisplayPort | 2 |
| DVI | 1 (DVI-D) |
| Serial (RS-232) | optional: serial port (9pin, 16 byte FIFO, 16550 compatible) |
| | |

| Interfaces | |
|------------------------------|--|
| Mouse / Keyboard (PS/2) | 0/1 optional (with PC on/off function on Pin6) |
| Ethernet (RJ-45) | 1 |
| Interface Module notes | Anytime USB charge functionality |
| Kensington Lock support | 1 |
| Input device / components | |
| Input devices (optional) | Keyboard |
| input devices (optional) | Mouse |
| | KBPC PX ECO |
| | Mouse M440 ECO |
| Drive bays | |
| Drive bays total | 2 |
| 2.5-inch internal bays | 1 |
| 5.25-inch external bays | 1 |
| Drive bay notes | 5.25" bay: for slim optical disc drive only |
| M.2-2280 | 1 x on mainboard for SSD NVMe (PCle 2.0 x2; up to 10Gbit/s) |
| Mini PCI slots | |
| M.2-2230 | on mainboard for WLAN module |
| Graphics on board | |
| Graphics brand name | Intel® UHD Graphics 610, Intel® UHD Graphics 630 |
| Shared video memory | Up to half size of total system memory |
| TFT resolution (DVI) | 1,280 x 1,024 pixel |
| (5.1) | 1,360 x 768 pixel |
| | 1,440 x 900 pixel |
| | 1,600 x 900 pixel 1,680 x 1,050 pixel |
| | 1,920 x 1,080 pixel |
| | 1,920 x 1,200 pixel |
| TFT resolution (DisplayPort) | 1,280 x 1,024 pixel |
| | 1,360 x 768 pixel |
| | 1,440 x 900 pixel 1,600 x 900 pixel |
| | 1,680 x 1,050 pixel |
| | 1,920 x 1,080 pixel |
| | 1,920 x 1,200 pixel |
| | 2,560 x 1,440 pixel |
| | 2,560 x 1,600 pixel |
| | 3,440 x 1,440 pixel 3,840 x 2,160 pixel |
| | 4,096 x 2,304 pixel |
| Graphics features | Dual display support |
| | DirectX® 12 |
| | HDCP support |
| | OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.5 |
| | DisplayPort interface supports Ver. 1.2 incl. Multi-Stream |
| | DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not |
| | included) |
| Graphics notes | up to 1 GB dedicated video memory (main memory owned and locked for graphics use) |
| | Tested resolutions, depending on display type additional resolutions and frequencies possible |
| | Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) |
| | For TFT we recommend using 60Hz |
| Electrical values | • |
| Power efficiency note | power supply efficiency (at 230V; 2 Watt/ 10% / 20% / 50% / 100% load) : > 85%/ 90% / 90% / 92% / 92% |
| Rated voltage range | 100 V - 240 V |
| nated voltage lalige | IOU Y ZTU Y |

| -1 | |
|--|---|
| Electrical values | |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | 65 W (integrated in system) |
| Power factor correction/active power | No (meets input harmonic current according EN61000-3-2) |
| Power consumption | |
| Power consumption note | See white paper Energy Consumption |
| Link to Energy White Paper | http://docs.ts.fujitsu.com/dl.aspx?id=51a9ac25-4489-41f0-afcf-386a82abfcb6 |
| Heat dissipation | |
| Heat dissipation notes | See white paper Energy Consumption |
| Noise emission | 1 1 3/1 1 |
| Related Processors for noise | Intel® Core™ i7 8700T |
| Standard noise emission | 2x4 GB, SSD, ODD, Windows |
| Standard Horse Guitzzion | According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position |
| Standard noise operation mode: HDD load | 3.0 B / 17 dB(A) Bystander; 16 dB(A) Operator position |
| Standard noise operation mode: Idle mode | 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position |
| Standard noise operation mode: ODD load | 4.4 B / 30 dB(A) Bystander; 34 dB(A) Operator position |
| Standard noise operation mode: Office applications 2.0 | 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position |
| Dimensions / Weight / Environmental | |
| Dimensions (W x D x H) | 185 x 190 x 54 mm; with VESA cover: 185 x 190 x 56.2 mm |
| | 7.29 x 7.49 x 2.13 inch |
| Operating position | Vertical / horizontal (no feet needed) |
| VESA mount | optional VESA cover required |
| Weight | 1.6 kg |
| Weight (lbs) | 3.53 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |
| Compliance | |
| Product | ESPRIMO Q558 |
| Model | MPC3 |
| Germany | TÜV GS |
| Europe | CE |
| USA/Canada | FCC Class B cTUVus |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) TCO Certified Desktop EPEAT® Bronze (dedicated regions) ENERGY STAR® 8.0 |
| China | CCC (planned) CCC (depending on configuration) CEL (Chinese energy label) TPM 2.0 for China (optional) |

| Compliance | |
|------------------------------------|--|
| Compliance notes | This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Additional Software | |
| Additional software (preinstalled) | Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |
| Manageability | |
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |
| DeskView components | BIOS Management incl. Security Inventory Management Driver Management Alarm Management |
| Supported standards | DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model) |
| Manageability link | http://www.fujitsu.com/fts/manageability |
| Security | |
| Physical Security | Kensington Lock support Eye for padlock Housing Lock Spring (to use with Kensington lock), (optional) |
| System and BIOS Security | Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) AuthConductor Client Basic (secure authentication solution) |
| Workplace Embedded Tools | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection |

| Miscellaneous | |
|--|--|
| Miscellaneous | Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management Low Power Active Mode Extended lifetime |
| Accessories information | Further helpful options Desktop Accessories: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/ Stands and Mounting kits: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html |
| | Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf |
| Serviceability | EasyChange for HDD EasyChange for optical drives |
| Packaging information | |
| Packaging dimension (mm) | 395 x 198 x 284 mm |
| Packaging dimension (inch) | 15.55 x 7.8 x 11.18 inch |
| Max. quantity / pallet | 84 |
| Material - Weight (g) Carton | 670 g |
| Material - Weight (lbs) Carton | 1.48 lbs |
| Material - Weight (g) EPS / PS | 10 g |
| Material - Weight (lbs) EPS / PS | 0.02 lbs |
| Material - Weight (g) PE | 125 g |
| Material - Weight (lbs) PE | 0.28 lbs |
| Packaging notes | If keyboard is inlcuded in packaging: 1.) packaging dimension is increasing to: $500 \times 208 \times 290 \text{mm} / (19.69 \times 8.19 \times 11.42 \text{ inch})$; 2.) material weight of carton will increase to $880g$; 3.) max. quantity/pallet = 56 ; printed user documentation is bleached in chlorin free process; |
| Warranty | |
| Warranty period | 1 year (for countries in EMEIA) |
| Warranty type | Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions Product Support Services - the perfec | http://www.fujitsu.com/warranty tt extension |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | 5 years after end of product life 5 years |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |
| | |

Recommended Accessories

Mounting Kit for Height Adjustable FUJITSU Displays



The FUJITSU Mounting Kit for Height Adjustable FUJITSU Displays has been specifically designed for use with ESPRIMO Q/G mini PCs, FUTRO Thin Clients and FUJITSU Displays. By mounting an ESPRIMO mini PC or a FUTRO Thin Client behind a display, you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Keyboard KB950 Phone



The KB950 Phone is a modern and slim line USB keyboard with integrated S26381-F950-L4** (**: Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO Q558, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO Q558, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-01-02 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH