Fujitsu recommends Windows 10 Pro for business.



# Data Sheet FUJITSU Desktop ESPRIMO D7010

New small form factor PC in a more compact and space-saving design

The FUJITSU ESPRIMO D7010 Desktop is a high performance, secure small form factor PC with ultimate expandability, along with best-in-class connectivity. Faster operations and a new housing helps in space saving to create the perfect working desk. The USB Type C, flexible graphics options offers great connectivity. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

### Latest Intel® Chipset technology and higher memory speed

High performance ensures faster operations and lower system response time

■ Intel® B460 chipset with higher memory frequency of 2,933 MT/s

#### New housing and ultimate expandability

Easily customizable and expandable small form factor PC that enables more space saving

- 2x low profile (LP) or 1x LP/ 1x Full height (Riser) via BTO
- Space saving in width and depth with new 8.3 litres volume

#### Best-in-Class connectivity

Be flexible and stay productive in a hyper-connected world

- A Support of new USB Type C in front
- Flexible graphics options (VGA, DVI-D, HDMI, Type C)
- USB Type C support of 60W (optional to power a display)
- Legacy PS2, serial port, parallel port connectors as option

#### High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Cable cover in addition to existing Smartcard reader, Erasedisk software
- Integrated Cabinet lock with Master key option
- Hole for pad lock and Kensington as standard for security

#### Low Power Consumption; Easy serviceability and usability

Reduced environmental impact and reduced energy bills; Features designed for easy access, control and use of the system

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Tool-less access to components, easy change and Screw-less add on cards









# Components

Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home
Operating system notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com.
Processor	Intel® Core™ i9-10900 processor (10 Cores / 20 Threads, 2.80 GHz, 20 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i7-10700 processor (8 Cores / 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i5-10600 processor (6 Cores / 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10500 processor (6 Cores / 12 Threads, 3.10 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10400 processor (6 Cores / 12 Threads, 2.90 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i3-10100 processor (4 Cores / 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) *
	Intel® Celeron® processor G5905 (2 Cores / 2 Threads, 3.50 GHz, 4 MB, Intel® UHD Graphics 610)
	Intel® Pentium® Gold G6400 (2 Cores / 4 Threads, 4.00 GHz, 4 MB, Intel® UHD Graphics 610)
	*with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other
	variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)
Memory modules	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
Mass storage 2.5 inch size	SSD SATA III, 512 GB, 2.5-inch
•	SSD SATA III, 256 GB, 2.5-inch
Mass Storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module, SED
-	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module, SED
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module, SED
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
Mass storage 3.5 inch size	HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch
Mass storage 2.5 inch size	HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	NVIDIA® Quadro® P400 LP, 2 GB
	NVIDIA® GeForce® GTX 1650
	MiniDP to DP Adapter Cable
Drives (optional)	BD Triple Writer SATA ultra slim (tray)
Drives (optional)	DVD Super Multi ultra slim (tray)
	SD Card reader

Interface add on cards/components (optional)	
	Gigabit Ethernet PCle x1
	WLAN 802.11ax (2x2) PCIe x1 LP and Bluetooth 5.0, SRD 5.8GHz (dedicated regions only)
	Dual serial card PCIe x1 LP

## Base unit

Base unit	ESPRIMO D7010
Mainboard	
Mainboard type	D3823-A2
Formfactor	proprietary
Chipset	Intel® B460
Processor socket	LGA 1200
Processor quantity maximum	1
Supported capacity RAM (max.)	128 GB
Memory slots	4 DIMM (DDR4)
Memory frequency	2,933 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Realtek RTL8111H
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC623
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	4
thereof SATA III	4
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-out	1
Front audio: headset	1
USB 2.0 total	4
USB 3.2 Gen 1 (5 Gbps) total	6 and 1 optional
USB 3.2 Gen 2 (10 Gbps) total	2
USB front	2x USB 2.0; 1x USB 3.2 Gen 1; 1x USB 3.2 Gen 2; 1x USB 3.2 (Gen 2) Type-C (supports up to 15W)
USB rear	2x USB 2.0; 4x USB 3.2 Gen 1; optional: additional 1x USB 3.2 Gen 1 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15W or 60W (occupies PCIe x16 slot)
USB internal	1x USB 2.0 or 1x USB 3.2 Gen 1 Type A
VGA	optional
DisplayPort	2
DVI	optional (DVI-D)

1(	
Interfaces	4/ **   1 **   40 **   46  **   550   46550 ***   **   **   **
Serial (RS-232)	1 (optional serial port (9pin, 16 byte FIFO, 16550 compatible))
Mouse / Keyboard (PS/2)	2 (optional)
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
Interface Module notes	Anytime USB charge functionality
Kensington Lock support	1
Input device / components	
Input devices (optional)	Keyboard Mouse
Drive bays	
Drive bays total	3
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	1x internal 3.5" bay optional (screwless), can be used via adapter for 1x or 2x 2.5" drives (screwless); 5.25" bay: for slim optical disc drive only;
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s)
Slots	
PCI-Express 3.0 x4 (mech. x16)	1 x (150 mm / 5.91 inch)
PCI-Express 3.0 x16	$1 \times (210 \text{ mm} / 8.27 \text{ inch})$ Low profile or full height (via Riser card), optional
Graphics on board	
Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel
TFT resolution (DVI)	up to 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 pixel (30 Hz)
Graphics features	Support for up to three independent displays  DirectX® 12  HDCP support  OpenCL™ 2.1  OpenGL® 4.5  For multi monitoring mode, graphics card and integrated graphics run in parallel  DisplayPort interface supports Ver. 1.4 incl. Multi-Stream  Digital audio formats are supported, including Dolby Digital Plus (7.1 channels)  DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included)  Additional I/O connectors configurable, choice of  DVI-D  HDMI™  VGA  USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)  USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies PCIe x16 slot)
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values	
Power efficiency note	Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD:
	for 230V ; 87/90/92/91
	for 115V ; 86/89/91/88
	80Plus PLATINUM:
	for 230V ; 88/92/94/93
	for 115V; 87/91/92/91
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	GOLD: 280W; PLATINUM: 300 W
Power factor correction/active power	active
Monitor outlet	Switched for PLATINUM power supply
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	https://docs.ts.fujitsu.com/dl.aspx?id=5d83ba46-8367-4613-9cee-40166b474f79
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise emission	
Related Processors for noise	Intel® Core™ i9-10900 processor and
	128GB, ODD; Windows 10 (tower position)
Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU	for GOLD PSU:
50% load	3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2) 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode: HDD	for GOLD PSU:
load	3.1 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
	3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode: Idle	for GOLD PSU:
mode	3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2) 3.3 B / 20 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode: ODD	for GOLD PSU:
load	4.5 B / 31 dB(A) Bystander; 37 dB(A) Operator position (SSD M.2)
	4.5 B / 32 dB(A) Bystander; 36 dB(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode: Office	for GOLD PSU:
applications 2.0	3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2) 3.3 B / 20 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2 and 3.5" HDD)
Dimensions (Wet-by UE- 1	5.5 5. 25 55( ) Systemoch 21 55( ) Speciator position (555 miz and 5.5 Hob)
Dimensions / Weight / Environmental  Dimensions (W x D x H)	314 x 296 x 89 mm
ען אווויוטווט (א א א די	12.36 x 11.65 x 3.51 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	approx. 8 kg
Weight (lbs)	арргох. 17.64 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)
Compliance	· · · · · · · · · · · · · · · · · · ·
Product	ESPRIMO D7010
Model	DTG
Germany	TÜV GS
comony	101 05

Compliance	
Еигоре	CE
USA/Canada	FCC Class B cTUVus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0, depending on configuration TCO Certified 8.0 (depending on configuration) EPEAT® Silver (dedicated regions), depending on configuration ENERGY STAR® compliance is an order option. Non ENERGY STAR/ TCO/ EPEAT compliant products are marked at branch name with additional suffix "n".
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces

Security	
User Security	User and supervisor BIOS password
oser security	Hard disk password
	Access protection via external SmartCard reader (optional)
	Access protection via internal SmartCard reader (optional)
	AuthConductor Client Basic (secure authentication solution)
Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required)
	Keyboard on with one key (KBPX Eco, KB521)
	Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards
	Keyboard on with any key (USB)
	Thermal management Extended lifetime
	Internal dust filter (optional)
Conviceshility	
Serviceability	EasyFix
	EasyChange for single 3.5" HDD (optional)
	EasyChange for optical drives
Packaging information	
Packaging dimension (mm)	499 x 296 x 439 mm
Packaging dimension (inch)	19.65 x 11.65 x 17.28 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1117 g
Material - Weight (lbs) Carton	2.46 lbs
Material - Weight (g) EPS / PS	225 g
Material - Weight (lbs) EPS / PS	0.5 lbs
Material - Weight (g) PE	25 g
Material - Weight (lbs) PE	0.06 lbs
Packaging notes	printed user documentation is bleached in chlorine free process; Bulk packagaging for projects (optional)
Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Warranty Terms & Conditions Product Support Services - the perfec	http://www.fujitsu.com/warranty t <mark>extension</mark>
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

## Recommended Accessories

### More information

#### Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO D7010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### **Computing Products**

www.fujitsu.com/global/products/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about FUJITSU Desktop ESPRIMO D7010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



#### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-02-04 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH