

Data Sheet FUJITSU Display E22-8 TS Pro

All-round widescreen Display 54.6 cm (21.5 inch)
Combines optimum performance with energy savings and ergonomics

The FUJITSU Display E22-8 TS Pro is an all-round business monitor that has In-Plane Switching (IPS) technology with 178°/178° wide viewing angle enabling you to see sharp pictures consistently from any perspective. The E22-8 TS Pro has a 1920 x 1080 Full HD (FHD) resolution delivering 16.7 million colors and comes with an ECO function that helps reduce the brightness to optimal levels in an office setting.

High performance FHD resolution monitor that delivers consistent clarity from any perspective

In-built speakers and multiple connectivity options for a modern office setting

Environment-friendly display that fulfills the Energy Efficiency A+ Class label and ENERGY STAR $^{\circ}$ compliance

Representative design providing a slender housing in ergonomic matt black with integrated speakers and power supply

Support for FUJITSU Desktop ESPRIMO Q and FUJITSU Thin Clients FUTRO backpack solutions













Technical details

	In-Plane Switching (IPS) technology, LED backlight panel, Eco button for Eco mode and 3-coloured Eco status LED, Keep aspect ratio option, Headset connector, Integrated speakers
Ergonomic stand	
Stand	removable
Picture height over desk (min)	63 mm
Picture height over desk (min)	63 mm
ilt angle	-5° / +22°
Picture performance	
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
iewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2
ize and resolution	230 (6)1112
spect ratio	16:9
Diagonal Size	54.6 cm (21.5-inch)
Resolution (native)	1,920 x 1,080 pixel
· · · · · · · · · · · · · · · · · · ·	
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 64 x 480 pixel
icture size	476 x 268 mm
ixel Pitch	0.248 mm
requencies	
lorizontal	30 - 82 kHz
ertical	56 - 76 Hz
onnectivity	
DisplayPort	1 x DisplayPort
OVI	1 x DVI-D (HDCP)
'GA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
audio sound output	2 x 1.5 W
hudio signal input	3.5 mm stereo phone jack
DisplayPort audio	Yes
ase-of-use menu	
Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
anguages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Node	sRGB, Office, Photo, Video, Low Blue Light
olor	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)
SD	Language, OSD-Timeout, OSD rotation
nage adjust	Clock, Phase, H-Position, V-Position, Expansion
	Mute, Volume, Input for DP interface
udio	·
nformation	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status
Advanced settings	Overdrive, DDC/CI, Factory Recall
Power consumption (typical, w/o sour	
Soft switch off	0.11 W

Power save mode	0.14 W
Operating with EPA settings	11.23 W
Total Energy Consumption (ETEC)	
Operating maximum brightness	35.23 kWh/year 26 W
Power supply	
Power notes	integrated Spanish of the state
Power notes	Speakers off ETEC and EPA refer to ENERGY STAR® 8.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Product	E22-8 TS Pro
Model	DY22-8T
Global	TCO Certified Displays 8.0, ENERGY STAR® 8.0, EPEAT® Bronze (dedicated regions), TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I)
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	RCM
China	CCC
Germany	TÜV GS
India	BIS
Russia	EAC
Singapore	S-Mark
South Korea	KC, E-Standby
Taiwan	BSMI
USA/Canada	FCC Class B, cUL
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	1 1 7
Dimension without stand (W x D x H)	500.5 x 55.75 x 298.28 mm
Simension without study (W X D X II)	19.70 x 2.19 x 11.74 inch
Dimension with stand (W x D x H)	500,5 x 212 x 343.45 mm
	19.70 inch x 8.35 x 13.52 inch
Weight (unpacked)	2.98 kg
weight (unpacked)	6.57 lbs
Weight (Monitor only)	2.68 kg
reight (monitor only)	5.91 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	10 00 % frion condensing)
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Black
Package content	DIOCN
Display delivered accessories	DVI-D Data cable 1.8 m
Display delivered accessories	D-SUB Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables detachable on display User manual is available via download
Packaging dimension (mm)	
Weight (packed)	4.29 kg

Weight (packed) (lbs)	9.46 lbs
Order information	
Order Code	S26361-K1603-V160
EAN Code	4057185709170
Country specific order code	BDL:K1603V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1603V160-CHN - with China power cable and CEL, mandatory for China BDL:K1603V160-ID - with Import label, mandatory for Indonesia (on demand) BDL:K1603V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed BDL:K1603V160-IND - with India power cable and BIS certificate, mandatory for India
Accessories information	Further helpful options: Stands and Mounting kits: http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life 5 years
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display E22-8 TS Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display E22-8 TS Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/ peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2021 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-02-04 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2021 Fujitsu Technology Solutions GmbH